



SYSTEM SCHEMATIC

SYSTEM NOTES

- SEPTIC TANKS SHALL HAVE A MINIMUM 1000 GAL. CAPACITY.
- COMBINED GREASE TRAPS SHALL HAVE A MINIMUM 1000 GAL. CAPACITY.
- MINIMUM SLOPE ON GRAVITY PIPES TO DISPOSAL FIELD 1%
- IF A PUMP IS USED SIZE PIPE AS RECOMMENDED BY PUMP MANUFACTURER.
- DIVERT SURFACE WATER AWAY FROM DISPOSAL FIELD.
- VEHICULAR OR LIVESTOCK TRAFFIC IS NOT ALLOWED ON DISPOSAL FIELD. THE DISPOSAL FIELD SHALL BE FENCED.
- SEPTIC TANKS AND GREASE TRAPS SHALL BE INSPECTED AND CLEANED REGULARLY, PARTICULARLY THE FAT ACCUMULATION.
- EMULSIFIER SOAPS SHALL NOT BE USED IN CONJUNCTION WITH THE MILK HOUSE WASTE WATER TREATMENT SYSTEM.

* STANDARDIZED DESIGNS MUST BE ADAPTED TO THE SPECIFIC SITE.



MILKING CENTER WASTEWATER TREATMENT SYSTEM SCHEMATIC

Designed _____	Date _____	File Name _____
Drawn <u>STANDARD</u>	Checked _____	Drawing Name <u>ME-ENG-MWW1</u>
Approved _____	Rev. <u>02/2010</u>	Sheet _____ of _____