



TABLE OF QUANTITIES

| "W" FEET | POLYETHYLENE SHEET SQ. FT. | CONNECTING BAND INCHES (MIN.) | STAINLESS STEEL CLAMPS | NUMBER OF 1/4" x 1" BOLTS |
|-------------|-------------------------------|----------------------------------|---------------------------|------------------------------|
| 4 | 17 | 6 | 2 | 6 |
| 5 | 26.3 | 6 | 2 | 6 |
| 6 | 37.5 | 6 | 2 | 6 |
| | | | | |

NUMBER OF ANTISEEP COLLARS REQUIRED = _____

NOTES:

1. THE PIPE, CONNECTING BAND, AND SEAM COATING CAN BE EITHER SILICON CAULKING (RECOMMENDED), TAR OR MASTIC.
2. APPLY SILICON CAULK, TAR, OR MASTIC TO THE CONNECTING BAND AND LAY THE PIPE ON IT. APPLY SILICON CAULK, TAR, OR MASTIC TO THE OTHER HALF OF THE CONNECTING BAND AND SET IT IN PLACE, LINING UP THE BOLT HOLES.
3. INSTALL THE STAINLESS STEEL CLAMPS ON THE SPLIT HALVES OF THE CONNECTING BANDS AND TIGHTEN THE BOLTS AND CLAMPS.
4. APPLY SILICON CAULK, TAR, OR MASTIC ON THE SEAMS AS NEEDED TO INSURE A GOOD SEAL SO THAT THE COMPLETED INSTALLATION IS WATERTIGHT.