



UPSTREAM ELEVATION

PIPE DIAM. (INCHES)	H (INCHES)	W (INCHES)	D (INCHES)
4	36	48	9.5
6	36	48	9.5
8	36	48	9.5
10	36	48	13.5
12	36	48	13.5

Notes:

1. THE NECK PORTION OF THE ANTISEEP COLLAR SHALL FACE UPSTREAM.
2. SLIDE THE FERNCO-TYPE OR EQUIVALENT ADAPTER ON THE PIPE TO BE INSTALLED. SLIDE THE PIPE THROUGH THE ANTISEEP COLLAR OPENING AND BELL. SLIDE THE ADAPTOR OVER THE ANTISEEP COLLAR NECK.
3. TIGHTEN THE STAINLESS STEEL CLAMPS ON THE ANTISEEP COLLAR NECK.
4. APPLY SILICON CAULK AS NEEDED TO INSURE A GOOD SEAL SO THAT THE COMPLETED INSTALLATION IS WATERTIGHT.

NUMBER OF ANTISEEP COLLARS REQUIRED = _____



**ABS ANTISEEP COLLAR
FOR 4"-12" DIAMETER PIPE**

CLIENT: _____
COUNTY: _____

Date _____
Designed _____
Drawn _____
Checked _____
Approved _____

File Name: WI-246-B
Date: 5/2008
Sheet of _____