



SLAB FOOTING CORNER DETAIL

NOTES FOR FOOTING STEEL PLACEMENT

- 1.) FOOTING TEMPERATURE AND SHRINKAGE STEEL (T&S) TO BE EXTENDED INTO THIS REGION FROM BOTH SIDES OF CORNER. REGION IS OUTSIDE EXTENSION OF WALLS INCLUDING WALL THICKNESS.
- 2.) STRENGTH STEEL IS EXTENDED INTO THIS REGION FROM BOTH SIDES OF CORNER. REGION IS INSIDE EXTENSION OF THE WALLS. FOOTING SLAB T&S STEEL OUTSIDE THE CORNER REGION TO LAP SPLICE WITH THE STRENGTH STEEL 16 INCHES.
- 3.) IN BOTH CORNER REGIONS, STRENGTH STEEL AND T&S STEEL WILL REQUIRE SWITCHING POSITIONS FROM TOP TO BOTTOM AND VICE VERSA.



United States
Department of
Agriculture

Natural Resources
Conservation Service

SLAB CORNER DETAILS

CLIENT: _____
COUNTY: _____

Designed _____	Date _____
Drawn _____	
Checked _____	
Approved _____	

File Name WI-571
Date 07/14
Sheet _____ of _____