



QUANTITIES	
HAND SHAPING _____	AS NEEDED
GRAVEL _____ (1/4" MIN. TO 3/4" MAX.)	_____ TONS
	OR
	_____ CU. YDS. *

\* (APPROX. 2.2 TONS PER 10 LIN. FT.)

NOTES:

1. THE TOP OF THE GRAVEL SPREADER MUST NOT VARY MORE THAN ONE-TENTH OF A FOOT FROM LEVEL.
2. BUILD THE WASTEWATER TREATMENT STRIP TO FINISHED GRADE, THEN BUILD THE GRAVEL SPREADER.
3. THE GRAVEL MUST BE CLEAN CRUSHED ROCK OR WASHED GRAVEL GRADED BETWEEN THE LOWER AND UPPER SIZE LIMITS.
4. REGRADE THE GRAVEL WHEN EVER NEEDED.
5. CLEAN OUT THE AREA ABOVE THE GRAVEL SPREADER AS NEEDED.



United States  
Department of  
Agriculture

Natural Resources  
Conservation Service

GRAVEL SPREADER

CLIENT: \_\_\_\_\_  
COUNTY: \_\_\_\_\_

Date \_\_\_\_\_  
Designed \_\_\_\_\_  
Date \_\_\_\_\_  
Drawn \_\_\_\_\_  
Checked \_\_\_\_\_  
Date \_\_\_\_\_  
Approved \_\_\_\_\_

File Name  
WI-595  
Date  
07/14  
Sheet of \_\_\_\_\_