

Construction Specification 31    Material Specification 535

Watershed \_\_\_\_\_ Site No. \_\_\_\_\_ Contract No. \_\_\_\_\_

Bid Schedule No. \_\_\_\_\_ Quantity \_\_\_\_\_ cubic yards

Contractor \_\_\_\_\_

Address \_\_\_\_\_

\_\_\_\_\_

**Information below is to be completed by the contractor or supplier**

Brand Name \_\_\_\_\_

Manufacturer \_\_\_\_\_

Address \_\_\_\_\_

\_\_\_\_\_

Supplier \_\_\_\_\_

Address \_\_\_\_\_

\_\_\_\_\_

Reference Specs  
ASTM D 1751

Bituminous 3/4-inch Thick:

Extrusion ( $\leq 0.25$  inch) \_\_\_\_\_ inches

Asphalt Content ( $>35\%$ ) \_\_\_\_\_ %

Density ( $>18$  pounds/cubic foot) \_\_\_\_\_ lbs/cu ft

Water Absorption (15% maximum) \_\_\_\_\_ %

Compression ( $\geq 100$  psi,  $\leq 750$  psi) \_\_\_\_\_ psi

Dimensions:

Thickness =  $\pm 1/16$  inch \_\_\_\_\_  $\pm$  inches

Depth =  $\pm 1/8$  inch \_\_\_\_\_  $\pm$  inches

Length =  $\pm 1/4$  inch \_\_\_\_\_  $\pm$  inches

This item meets standard requirements in the current specifications of the American Society for Testing and Materials (ASTM) as listed above.

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Date

\_\_\_\_\_  
Title