



**Natural Resources Conservation Service**  
**CONSERVATION PRACTICE STANDARD**  
**FISH RACEWAY OR TANK**

CODE 398

(no)

**DEFINITION**

A channel or tank with a continuous flow of water used for high-density production of fish or other aquatic organisms.

**PURPOSE**

This practice is used to accomplish one or more of the following purposes:

- Design an aquaculture facility to supply water of suitable temperature, quantity, and quality to meet the basic needs of farmed fish and other aquatic organisms.
- Manipulate chemical, physical, and biological factors to treat effluents before release into receiving waterbodies.

**CONDITIONS WHERE PRACTICE APPLIES**

This standard applies to aquaculture raceways or tanks that convey flowing or recirculating water to produce fish or other aquatic organisms. This includes earthen channels as well as channels and tanks constructed of concrete, concrete block, timber, rock, fiberglass, or other materials.

**CRITERIA**

**General Criteria Applicable to All Purposes**

Design a facility to provide protection from flooding, sedimentation, and contamination by pollutants from outside sources.

Design raceway or tank dimensions based upon the legally available water and planned production level. Meet all applicable Federal, State, territorial, Tribal, and local laws and regulations.

**Water quantity entering facility**

Maintain a water supply of sufficient volume and appropriate temperature, either by gravity flow or by pumping, to produce the desired species. Generally, this amount would equate to two complete water exchanges per hour for a raceway length of 80 to 100 feet (ft) but some systems

NRCS reviews and periodically updates conservation practice standards. To obtain the current version of this standard, contact your Natural Resources Conservation Service State office or visit the Field Office Technical Guide online by going to the NRCS website at <https://www.nrcs.usda.gov/> and type FOTG in the search field.

**USDA is an equal opportunity provider, employer, and lender.**

NRCS, NHCP  
Month Year

may require less water. Measure the water volume during periods of low flow.

#### **Water quality entering facility**

Supply water free of (or at acceptable levels for species-specific biological needs) harmful gases, sediments, minerals, silt, nutrients, pathogens, pesticides, and other contaminants. Conduct a water analysis before design and construction unless previous use or experience indicates water quality is satisfactory for the desired species. Consult Land Grant University recommendations for species-specific water quality requirements.

#### **Vegetation**

During construction, stockpile topsoil for placement on disturbed areas to facilitate revegetation. Consider selecting and placing vegetation to improve fish and wildlife habitat, and species diversity.

#### **Predator control**

As needed, provide fences, screens, nets, wires, or other materials to prevent the loss of fish and other aquatic organisms to predators. Place traps or other devices potentially harmful to humans, livestock, or pets in secure locations not normally accessible except through special effort. A State agency may require a license or permit to perform such activities.

#### **Waste (effluent) Management in Flow Through Systems**

Develop plans for the treatment of wastewater generated or caused by the operation of aquaculture raceways or tanks before effluent release into receiving waterbodies. Consult the National Engineering Handbook, Part 651 – Agricultural Waste Management Field Handbook for details.

Such plans may include the construction of NRCS Conservation Practice Standard (CPS) Waste Treatment Lagoons (Code 359), Constructed Wetland (Code 656), or other facilities.

Solid waste handling - Apply and spread of solid waste in accordance with CPS Nutrient Management (Code 590). Export of excess waste according to CPS Waste Recycling (Code 633). Solids that are collected in aquaculture systems can be composted similar to the composting of other animal wastes; refer to Compost Facility (Code 317) and the National Engineering Handbook, Part 637 Environmental Engineering, Chapter 2 Composting.

Final discharges into waterbodies must meet state and federal standards for the stream or other surface waters, based on the size of the operation, and comply with National Pollutant Discharge Elimination System (NPDES) regulations. For urban facilities, direct discharge into municipal sewer system must meet the local municipal wastewater quality requirements. Consult National Engineering Handbook, Part 650 – Engineering Field Handbook, Subpart T – Urban Agriculture for additional information.

#### **Criteria Applicable to Linear Channel Raceways**

Raceways generally consist of linear channels where water flows in at one end and exits at the other end. Linear channel raceways generally consist of two types:

- Concrete or concrete block construction—Design and construct raceways in accordance with NRCS National Engineering Manual, Part 536, “Structural Design.” When designing concrete or concrete block raceways, use the same design material for the bulkheads or check dams.
- Earthen channels construction with a trapezoidal or parabolic cross section—Design raceways with a trapezoidal or parabolic cross section. Design bottom widths based on the volume of water available, but not less than 4 ft. Design side slopes 1:1 or flatter, depending on a slope stability analysis. Design and construct side slopes and bottoms of

raceways with smooth and uniform surfaces to minimize dead water areas.

### **Grade**

Wherever possible, design and construct raceways with a minimum bottom grade of 0.5 ft per 100 ft. The raceway outlet will control the water surface grade.

### **Length**

Determine the maximum length of each raceway section by site topography and need for reaeration of the water, but no more than 100 ft. For the design of raceway sections in series, install a bulkhead or check dam at the lower end of each section.

### **Width**

Select the width of individual raceways considering the available water supply, harvesting equipment, and operation and maintenance needs of the system.

### **Freeboard**

The minimum difference in elevation between the water surface in the raceway and the top of the bulkhead, dike, or levee alongside the raceway is 0.5 ft.

### **Dikes and levees**

Design a 6-ft minimum top width for earthen dikes or levees. Use 2:1 or flatter side slopes for portions of earthen dikes and levees above the water surface. Use a 14-ft minimum top width and 3:1 or flatter side slopes when using the top of the dike or levee as a road.

### **Bulkheads**

Place structural or earthen barriers, called bulkheads, across raceway channels to create shorter sections, establish and maintain the desired water levels, and provide aeration of the water. In addition to serving as a barrier, they must have an opening or throat section that allows complete drainage to the bottom of the raceway channel unless other drainage facilities are provided.

Design bulkheads using earth, concrete, concrete block, rock masonry, steel or other durable metal, treated timber, or a combination of these as follows:

- Provide a minimum top width of 4 ft and side slopes of 2:1 or flatter for earthen bulkheads.
- Provide a minimum top width of 6 in and a minimum bottom width of 8 in for reinforced concrete bulkheads.
- Extend concrete, concrete block, rock masonry, or steel bulkheads used in earthen raceways at least 2 ft into the sides and bottom of the channel.
- Design the opening or throat section of bulkheads using concrete, concrete block, wood, or metal.
- Provide slots or grooves along the vertical face that allows installation of flashboards and screens.
- Fill openings and cores in concrete blocks with either concrete or a mortar mix.

### **Drains**

Provide a pipe drain with a minimum diameter of 6 in at the bottom of the bulkhead or provide for flashboard removal to allow complete drainage. Where possible, design each unit in a series to allow drainage independent of the other units.

### **Screens**

Provide screens at the inlet of the system, if necessary, to prevent wild fish (including wild, native species) from entering the production facility/operation and farmed fish from escaping into

natural waterbodies.

Screening design must meet state requirements and, where applicable, Federal requirements. Provide screens at each bulkhead between sections and at the exit end to prevent loss of fish. Place screens at least 6 to 8 in upstream from the flashboards and extend screens at least 6 to 8 in above the expected water level to prevent fish escape from jumping. Design screen openings based on the size range of fish requiring separation. Maintain water velocity through screens slow enough to prevent fish impingement on screens.

### **Aeration**

Fit each bulkhead with a weir overfall such as flashboards in the opening or throat section of the bulkhead. Design the width of the weir or weirs equal to the bottom width of the raceway, but not less than 4 ft where flashboards are used to establish the desired water level. Design two or more weirs separated by rigid center sections when the width of the raceway exceeds 8 ft. To increase aeration as part of the design, arrange a splash board or series of boards to create successive splashes or place nozzles in the tank above the water surface. Set the weir crest at least 1 ft above the downstream water surface elevation.

### **Criteria Applicable to Tanks**

Tanks generally have a circular, rectangular, or oval shape. Water enters a tank through nozzles or jets in a manner that creates a rotary circulation within the tank and typically discharges through the tank center by means of a standpipe or bottom drain.

Construct tanks using concrete, metal, fiberglass, or other suitable material capable of providing the strength and durability for the anticipated use. Noncircular tanks must have an interior dividing wall to obtain proper circulation. Construct tank raceways at locations accessible to water supplies, management personnel, and feed and harvest equipment.

### **Water supply**

Install jets, nozzles, or similar devices that provide a tangential force to the water in the tank. Locate submerged nozzles above the tank bottom to minimize the uplift of waste particles. In the Northern Hemisphere, position nozzles to direct flow counterclockwise.

### **Waste removal**

Incorporate provisions for waste removal in the design. Provide bottom troughs, screens, or center-positioned drainpipe as part of the tank construction.

## **CONSIDERATIONS**

### **General Considerations**

#### **Waste (Effluent) Management using Recirculating Aquaculture Systems (RAS)**

Consider a RAS approach, which includes among its purposes minimizing water use and allowing for secondary use of wastewater (e.g., re-use of water for fish, aquaponic crop, algae, or invertebrate production).

The RAS can also improve system efficiency, which reduces surface and/or groundwater withdrawal. For example, for situations where water scarcity is an issue (e.g., arid environments) or effluent water quality standards are limiting (e.g., urban agriculture, small-scale operations), consider developing a plan for the collection, treatment, and recirculation of effluent water generated by the aquaculture raceway or tank operation.

Essential components of a RAS include: effluent from the fish-rearing raceways or tanks; solids removal; biofilter or hydroponic component; and sump and/or return transfer to fish-

rearing component.

For additional planning and design of an RAS system, refer to National Engineering Handbook, Part 651, Agricultural Waste Management Field Handbook. Components may include the construction of NRCS Conservation Practice Standard (CPS) Waste Storage Structures (Code 313), CPS Waste Treatment Lagoons (Code 359), Irrigation System, Surface and Subsurface (Code 443), or other facilities. Spread waste in accordance with CPS Nutrient Management (Code 590); compost waste in accordance with Compost Facility (Code 317).

#### **Design facility for increased system efficiency to reduce energy use**

Consider assessment of the aquaculture system for energy efficiency. Additional energy efficiency practices include Energy Efficient Agricultural Operation (Code 374), Energy Efficient Building Envelope (Code 672), and Energy Efficient Lighting System (Code 670).

#### **Fish and wildlife**

Consider and minimize, to the extent possible, the impacts of cultivated nonnative fish on endemic fish populations, as well as potential interactions with wildlife and birds that can be attracted to these facilities.

#### **Water quantity**

Consider effects upon components of the water budget, such as—

- Volumes and rates of runoff, infiltration, evaporation, transpiration, deep percolation, and groundwater recharge.
- Variability of weather caused by seasonal or annual trends.
- The effects of water withdrawal on native aquatic organisms. This is especially critical during seasonal low stream flow.
- Downstream flows and impacts to environment such as wetlands, aquifers, and social and economic impacts to downstream uses or users.

#### **Water quality**

Consider the effects of—

- Erosion and the movement of sediment, pathogens, and soluble and sediment-attached substances that runoff carries.
- Short-term and construction-related effects of this practice on the quality of downstream watercourses.
- Water-level control on the temperatures of downstream water to prevent undesired effects on aquatic and wildlife communities.
- Water level on wetlands and water-related wildlife habitats.
- Water levels on soil nutrient processes such as plant nitrogen use or denitrification.
- Soil water level control on the salinity of soils, soil water, or downstream water.
- Potential for earth moving to uncover or redistribute toxic materials.
- Movement of dissolved organic and inorganic chemicals downstream and towards groundwater recharge areas.

### **PLANS AND SPECIFICATIONS**

Prepare plans and specifications that describe the requirements for applying the practice according to this standard. As a minimum, include—

- A plan view of the layout of the facility and appurtenant features.

- Typical profiles and cross sections of the facility and appurtenant features as needed.
- Structural drawings adequate to describe the construction requirements.
- Requirements for vegetative establishment and mulching, as needed.
- Safety features.
- Site-specific construction and material requirements.

## OPERATION AND MAINTENANCE

Prepare an operation and maintenance plan for the facility.

As a minimum, include the following items in the operation and maintenance plan:

- Periodic inspections of all structures, earthen embankments, and other appurtenances.
- Prompt repair or replacement of damaged components.
- Prompt removal of sediment when it reaches predetermined storage elevations.
- Periodic removal of trees, brush, and undesirable species.
- Periodic inspection of safety components and immediate repair if necessary.
- Maintenance of vegetative protection and immediate seeding of bare areas as needed.

## REFERENCES

American Society for Testing and Materials. Standard Practice for Classification of Soils for Engineering Purposes (Unified Soil Classification System), ASTM D2487. West Conshohocken, PA.

Mefford, B. 2014. [Pocket Guide to Screening Small Water Diversions](#). U.S. Bureau of Reclamation, Denver Technical Service Center.

National Marine Fisheries Service. 2022. [NOAA Fisheries West Coast Region Anadromous Salmonid Passage Design Manual](#), NMFS, WCR, Portland, Oregon.

Nordlund, B. 2008. [Designing Fish Screens for Fish Protection at Water Diversions](#). National Marine Fisheries Service.

Timmons, M.B., and B.J. Vinci. 2022. Recirculating Aquaculture 5th Edition. Ithaca Publishing Company. Ithaca, NY.

USDA NRCS. National Biology Manual. Washington, D.C.

USDA NRCS. National Engineering Handbook, Part 633, Soil Engineering. Washington, D.C.

USDA NRCS. National Engineering Handbook, Part 637, Environmental Engineering. Washington, D.C.

USDA NRCS. National Engineering Handbook, Part 650, Engineering Field Handbook. Washington, D.C.

USDA NRCS. National Engineering Handbook, Part 651, Agricultural Waste Management Field Handbook. Washington, D.C.

USDA NRCS. National Engineering Manual. Washington, D.C.

USDA Southern Regional Aquaculture Center. Regional Aquaculture Center Fact Sheets. Stoneville, MS. [srac.tamu.edu/](http://srac.tamu.edu/)