



CONSERVATION ENHANCEMENT ACTIVITY

E329144Z

CONSERVATION STEWARDSHIP PROGRAM

No till to reduce energy

Conservation Practice 329: Residue & Tillage Management, No Till

APPLICABLE LAND USE: Crop (Annual & Mixed)

RESOURCE CONCERN ADDRESSED: Inefficient Energy Use

ENHANCEMENT LIFE SPAN: 1 Year

Enhancement Description

Establish a no till system which reduces total energy consumption associated with field operations by at least 25% compared to current tillage system (benchmark). Each crop in the crop rotation shall have a Soil Tillage Intensity Rating (STIR) of no greater than 20. The current NRCS wind and water erosion prediction technologies must be used to document STIR calculations and energy consumption.

Criteria

- Residue shall not be burned.
- All residues must be uniformly distributed over the entire field. Removing residue from the row area prior to or as part of the planting operation is acceptable.
- No full-width tillage is performed from the time of harvest or termination of one cash crop to the time of harvest or termination of the next cash crop in the rotation regardless of the depth of the tillage operation.
- The Soil Tillage Intensity Rating (STIR) value must include all field operations that are performed during the crop interval between harvest or termination of the previous cash crop and harvest or termination of the current cash crop (includes fallow periods). Each crop must have a STIR value no greater than 20.



- Reduce the total energy consumption associated with field operations by at least 25% compared to the current benchmark tillage system. Use the current NRCS wind and water erosion prediction technologies for determining energy use to document energy use reductions.

CONSERVATION STEWARDSHIP PROGRAM





CONSERVATION STEWARDSHIP PROGRAM

Documentation and Implementation Requirements

Participant will:

- Prior to implementation, provide NRCS with the current (benchmark) and planned crop rotation and tillage operation(s) used for each crop.

Field	Acres	Current (Benchmark) Crops (in sequence)	Length of Crop Rotation (years)

Field	Crop	Current (Benchmark) Field Operation	Timing of Field Operation (month/year)

Field	Acres	Planned Crops (in sequence)	Length of Crop Rotation (years)

Field	Crop	Planned Field Operation	Timing of Field Operation (month/year)

- During implementation, notify NRCS of any planned changes in crops, crop rotation, or field operations to verify the planned system meets the enhancement criteria.



CONSERVATION STEWARDSHIP PROGRAM

- During implementation, no residue will be burned.
- During implementation, all residues will be uniformly distributed over the entire field. Removing residue from the row area prior to or as part of the planting operation is acceptable.
- During implementation, no full-width tillage may be performed from the time of harvest or termination of one cash crop to the time of harvest or termination of the next cash crop in the rotation regardless of the depth of the tillage operation.
- During implementation, reduce the total energy consumption associated with field operations by at least 25% compared to the current benchmark tillage system.
- After implementation, if changes to the rotation were made, complete the tables above to document the applied Conservation Crop Rotation for the contract period and provide to NRCS.

NRCS will:

- As needed, provide technical assistance to meet the criteria of the enhancement.
- Prior to implementation, use information provided from the participant to calculate the Soil Tillage Intensity Rating values and energy consumption for both the current system and the planned system using the approved NRCS wind and water erosion prediction technologies. Verify the Soil Tillage Intensity Rating value is no greater than 20 for each crop in the planned rotation and total energy consumption is reduced by at least 25%.

Current STIR values = _____ and Energy Consumption = _____

Planned STIR values = _____ and Energy Consumption = _____

- During implementation, evaluate planned changes in crops, crop rotation, or field operations to verify the planned system meets the enhancement criteria.
- After implementation, if changes were made to the planned crops, crop rotation, or field operations, use information provided from the participant to calculate the Soil Tillage Intensity Rating values and total energy consumption to document that the applied rotation met the enhancement criteria.

Applied STIR values = _____ and Energy Consumption = _____



NRCS Documentation Review:

I have reviewed all required participant documentation and have determined the participant has implemented the enhancement and met all criteria and requirements.

**CONSERVATION
STEWARDSHIP
PROGRAM**

Participant Name _____ Contract Number _____

Total Amount Applied _____ Fiscal Year Completed _____

NRCS Technical Adequacy Signature

Date





SOUTH DAKOTA (SD) SUPPLEMENT TO CONSERVATION ENHANCEMENT ACTIVITY E329144Z

CONSERVATION STEWARDSHIP PROGRAM

Additional Criteria for SD

- In addition to the criteria specified in the National job sheet E329144Z, the following additional criteria apply in SD:
- Utilize the table below to estimate energy savings from the existing cropping system to the planned no-till system. Energy savings must be 25 percent (%) or greater. Utilize RUSLE2 or current erosion prediction technology if operations needed are not listed.

Operation Name	Diesel use per area
Aerial interseeding	.00000001
Bale straw or residue	0.38
Chisel plow, coulter, st. pts.	1.2
Chisel plow, coulter, st. pts., cover disks, rlng basket	1.8
Chisel, st. pt.	1
Chisel, sweep shovel	1.1
Chisel, sweep shovel 5 in. depth, coil tine har	1
Coulter caddy, dbl gang w/ fluted coulters - Great Plains Turbo-till	0.35
Coulter tiller and spike harrow	0.85
Coulter tiller, 10 degree angle, coiled tine harrow, rolling basket - Salford RTS	0.85
Cultivator, field 6-12 in sweeps	0.74
Disk, tandem heavy primary op.	0.75
Disk, tandem light finishing	0.4
Drill or air seeder single disk openers, + fert. opnrs 7-10 in spac.	0.48
Fert applic. side-dress, liquid	0.13
Fert applic. surface broadcast	0.16
Fert. applic. anhyd knife 30 in	0.8
Fert. applic. anhyd, liq, dry, minimal dist. precision placmnt, 30 in	0.8
Fert. applic., strip-till 30 in	0.9
Harvest, killing crop 50pct standing stubble	1.53
Harvest, silage	0.95
Harvest, stripper header	1.53
Manure injector, liquid low disturb.30 inch	1.56
Manure spreader, liquid	1.23
Planter, double disk opnr	0.44
Planter, double disk opnr with starter fertilizer	0.65
Planter, strip till	0.62
Roller, smooth	0.25
Sprayer, post emergence and fert. tank mix	0.13
Sprayer, pre-emergence	0.13
Strip till bed conditioner	0.32



CONSERVATION STEWARDSHIP PROGRAM

Example:

Benchmark Rotation	Diesel Use
Cultivator, field 6-12 in sweeps	.74
Planter, double disk opnr	.44
Sprayer, pre-emergence	.13
Fert application, surface broadcast	.16
Sprayer, post emergence	.13
<u>Harvest crop</u>	<u>1.53</u>
Chisel, sweep shovel	1.1
Cultivator, field 6-12 in sweeps	1.0
Roller, smooth	.25
Planter, double disk opnr	.44
Sprayer, pre-emergence	.13
Sprayer, post-emergence	.13
<u>Harvest crop</u>	<u>1.53</u>
Diesel use for entire rotation	7.71

Planned Rotation	Diesel Use
Planter, double disk opnr w/fert	.65
Sprayer, pre-emergence	.13
Sprayer, post-emergence	.13
<u>Harvest crop</u>	<u>1.53</u>
Roller, smooth	.25
Planter, double disk opnr	.44
Sprayer, pre-emergence	.13
Sprayer, post-emergence	.13
<u>Harvest crop</u>	<u>1.53</u>
Diesel use entire rotation	4.92

To calculate energy savings, divide rotation diesel use by years in rotation to get average annual use.

Average Annual Use: $4.92/2 = 2.46$ (planned rotation) and $7.71/2 = 3.855$ (benchmark rotation)

Energy Savings: $1 - (2.46/3.855) * 100 = 36.2\%$ savings